



GRITTGEAR®



a) The following component parts, a description of each component part, and material/s used in each component part:

<p>i. Upper;</p> <p>ii. Insole (when used);</p> <p>iii. Insock (when used);</p> <p>iv. Outsole;</p> <p>v. Toecap;</p> <p>vi. Vamp lining;</p> <p>vii. Quarter lining;</p> <p>viii. Edge covering of the toecap;</p> <p>ix. Scuff resistant coverings for the toe region (when used);</p> <p>x. Collar and insert materials above the upper (when fitted);</p> <p>xi. Tongue;</p> <p>xii. Penetration-resistant insert (when fitted);</p> <p>xiii. Heat and/or cold insulation (when fitted);</p> <p>xiv. Metatarsal protective device (when fitted);</p> <p>xv. Cut resistant layer (when fitted);</p>	<p>Crazy Horse</p> <p>Antistatic non-metallic inserts</p> <p>Black nylon mesh with EVA with anti-static thread</p> <p>PU/Rubber</p> <p>Steel</p> <p>Non-woven fabric</p> <p>Nylon mesh</p> <p>TPU</p> <p>TPU 1.4mm</p> <p>N/A</p> <p>N/A</p> <p>Kevlar (antistatic non-metallic inserts)</p> <p>N/A</p> <p>N/A</p> <p>N/A</p>																		
<p>b) Upper:</p> <p>i. Height of the upper;</p>	<p>5 - 6 109mm</p> <p>7 - 8 113mm</p> <p>9 - 10 117mm</p> <p>11 - 12 121mm</p> <p>13 125mm</p>																		
<p>ii. Thickness of the material/s used in the upper;</p>	<p>1,6mm</p> <p>Closed seat region</p>																		
<p>c) Layout of the seat region;</p>																			
<p>d) Insole (when used):</p>																			
<p>i. Thickness of the insole;</p>	<p>2mm for all sizes</p>																		
<p>ii. Method of assembly of the insole to the footwear;</p>	<p>Subject to heat and pressure between heated platens</p>																		
<p>e) Type of insock (when used):</p>																			
<p>i. Non-removable insock, OR;</p>																			
<p>ii. Seat sock, OR;</p>																			
<p>iii. Full insock, non-removable, OR;</p>																			
<p>iv. Full insock, removable and water permeable, OR;</p>	<p>X - Full insock, removable and water permeable,</p>																		
<p>v. Full insock, removable, not water permeable;</p>																			
<p>f) Thickness of the insock (when used);</p>	<p>6-8mm for all sizes</p>																		
<p>g) Method of assembly of a non-removable insock to the footwear (when used);</p>	<p>Manual insertion, non-bound</p>																		
<p>h) Toecap:</p>																			
<p>i. Method of assembly of the toecap to the footwear;</p>	<p>Setting and bonding</p>																		
<p>ii. Internal length of the toecap;</p>	<p>5 - 6 39mm</p> <p>7 - 8 40mm</p> <p>9 - 10 41mm</p> <p>11 - 12 42mm</p> <p>13 43mm</p>																		
<p>iii. Minimum thickness of the material used in the toecap;</p>	<p>2mm</p>																		
<p>i) The position and all dimensions (including the thickness of the material used) of an edge covering under the back edge of the toecap;</p>	<table border="1"> <tbody> <tr> <td>5</td><td>6</td><td>7</td><td>8</td><td>9</td><td>10</td><td>11</td><td>12</td><td>13</td> </tr> <tr> <td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td><td>15</td> </tr> </tbody> </table>	5	6	7	8	9	10	11	12	13	15	15	15	15	15	15	15	15	15
5	6	7	8	9	10	11	12	13											
15	15	15	15	15	15	15	15	15											

j) Thickness of the scuff resistant coverings for the toe region;	5	6	7	8	9	10	11	12	13
	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3	2.3

- k) Outsole:
- i. Method of assembly of the outsole to the upper;
 - ii. Minimum thickness of the outsole (excluding cleats and heel);
 - iii. Cleat pattern (when used);

Injection moulded
2.5mm



iv. Length of the outsole;	5	284mm
	6	291mm
	7	298mm
	8	305mm
	9	312mm
	10	319mm
	11	326mm
	12	333mm
	13	340mm

- v. Minimum cleat height (when used);

3mm for all sizes

- l) For outsoles that consist of more than one layer:

i. Number of layers;	2
ii. Material used in each layer;	PU/Rubber
iii. Minimum thickness of each layer;	4mm
iv. Method of assembly of the different layers to each other;	Injection
i. Thickness of the penetration-resistant insert;	4.5mm
ii. Method of assembly and layout of the penetration-resistant insert in the footwear;	stitching
n) Heat and/or cold insulation (when fitted):	Not applicable
i. Thickness of the heat and/or cold insulation;	Not applicable
ii. Method of assembly of the heat and/or cold insulation to the footwear;	Not applicable
i. Thickness of the metatarsal protective device;	Not applicable
ii. Method of assembly of the metatarsal protective device to the footwear;	Not applicable
p) Cut resistant layer (when fitted):	Not applicable
iii. Thickness of the cut resistant layer;	Not applicable
iv. Minimum height of the cut resistant layer above the feather edge;	Not applicable
v. The minimum measurement of overlap of the cut resistant layer beyond the rear end of the toecap;	Not applicable
vi. Method of assembly of the cut resistant layer to the footwear.	Not applicable